

GEKA® plus hose trolley P80

Advantage / benefit: **Sturdy, powder-coated steel construction suitable for drinking water, the used components meet the German drinking water ordinance**
With eco-friendly powder coating
Optimized frame design for guaranteed stability and easy rolling
Safe interlock made from stainless steel: drum can be locked in 12 positions
Air-filled, gripping tyres for comfortable rolling
Curved intake tube prevents the hose from kinking
Optimal water throughput thanks to 1" fitting and 1" intake tube
With GEKA® plus 90° angled rotary fitting for drinking water, brass
Convenient accessory rack to hold a nozzle
Anti-slip toes with large contact surface for guaranteed stability

Material: Frame: powder-coated steel tubing (Ø 22mm + Ø 30 mm); Grip, Air-filled tyres: black rubber; Accessory rack: metal; Crank handle: green plastic; Intake tube: powder-coated stainless steel; GEKA® plus rotary fitting for drinking water: brass

Dimensions cm: 67 x 112 x 66

Please note: Pre-assembled, without hose or accessories; Spare parts available on demand



| | |
|--|------------------|
| Connection male thread to water tap mm | 33,25 |
| Connection male thread to water tap | G1 |
| Connection male thread at hose outlet mm | 33,25 |
| Connection male thread at hose outlet | G1 |
| Capacity 1/2"-hose approx. m | 150 |
| Capacity 5/8"-hose approx. m | 100 |
| Capacity 3/4"-hose approx. m | 80 |
| Capacity 1"-hose approx. m | 50 |
| Tyre pressure max. bar | 2,1 |
| Net weight approx. kg | 26 |
| Operating temperature °C | +4 to +60 |
| PU units | 1 |
| Catalogue no. | 8503SB |
| Item no. | 42.8503.9 |

5




Air-filled tyres for comfortable rolling



GEKA® plus rotary fitting for drinking water



180° curved intake tube prevents the hose from kinking



Locking of drum possible in 12 positions



Ergonomic construction: comfortable rolling



Hose protecting drum