

# GEKA® plus water hoses

## GEKA® plus water hoses 110

Advantage / benefit:.....5-layer hose design; Highest quality materials;  
Very pressure-resistant, highly flexible, does not warp or twist even when cold;  
smooth and dirt-repellent, resistant to light, weather and ozone; algae free;  
resistant to kinks, shocks, deformation and abrasion; comfortable handle  
15-year guarantee

Material:.....Core: high-quality, translucent PVC; Inner tricot inlay: polyester;  
Central layer: black PVC; Outer tricot inlay: extremely tear-resistant polyester thread;  
Cover: high-quality translucent PVC; Free of phthalate

Temperature range: .....approx. -10 °C to +50 °C

Colour: .....Translucent grey with dark grey matte stripes

Area of application: .....Very frequent use, heavy duty, nurseries, etc.

Packaging: .....Wrapped in film with a cardboard display disc and EAN code



Hose size Zoll	1/2"	1/2"	5/8"	5/8"
Hose LW mm	13	13	15	15
Hose OD mm	19	19	21	21
wall thickness mm	3	3	3	3
Length approx. m	25	50	25	50
Operating pressure at +20 °C bar	18	18	15	15
PU Units	1	1	1	1
Catalogue no.	152513SB	155013SB	152516SB	155016SB
<b>Item no..</b>	<b>15.0000.9</b>	<b>15.0001.9</b>	<b>15.0002.9</b>	<b>15.0003.9</b>

Hose size Zoll	3/4"	3/4"	1"	1"
Hose LW mm	19	19	25	25
Hose OD mm	26	26	33	33
wall thickness mm	3,5	3,5	4	4
Length approx. m	25	50	25	50
Operating pressure at +20 °C bar	12	12	10	10
PU Units	1	1	1	1
Catalogue no.	152519SB	155019SB	152525SB	155025SB
<b>Item no..</b>	<b>15.0004.9</b>	<b>15.0005.9</b>	<b>15.0006.9</b>	<b>15.0007.9</b>

5

## GEKA® plus water hoses 105

Advantage / benefit:.....5-layer hose design; High-quality materials;  
highly flexible, does not warp or twist even when cold; smooth and dirt-repellent;  
resistant to light, weather and ozone; algae free; kink, shock and abrasion proof; comfortable handle  
10-year guarantee

Material:.....Core: high-quality, white PVC; Second layer: matte yellow PVC;  
Central layer: polyester thread; Trico inlay: extremely tear-resistant knit polyester thread;  
Cover: high-quality translucent green PVC

Temperature range: .....approx. -10 °C to +50 °C

Colour: .....Translucent green with matte grey stripes

Area of application: .....Frequent use, heavy duty, nurseries, hobby gardeners

Packaging: .....Wrapped in film with a cardboard display disc and EAN code



Hose size Zoll	1/2"	1/2"	5/8"	5/8"
Hose LW mm	13	13	15	15
Hose OD mm	18	18	20	20
wall thickness mm	2,5	2,5	2,5	2,5
Length approx. m	25	50	25	50
Operating pressure at +20 °C bar	10	10	9	9
PU Units	1	1	1	1
Catalogue no.	142513SB	145013SB	142516SB	145016SB
<b>Item no..</b>	<b>14.0000.9</b>	<b>14.0001.9</b>	<b>14.0002.9</b>	<b>14.0003.9</b>

Hose size Zoll	3/4"	3/4"	1"	1"
Hose LW mm	19	19	25	25
Hose OD mm	25	25	33	33
wall thickness mm	2,5	2,5	4	4
Length approx. m	25	50	25	50
Operating pressure at +20 °C bar	8	8	6	6
PU Units	1	1	1	1
Catalogue no.	142519SB	145019SB	142525SB	145025SB
<b>Item no..</b>	<b>14.0004.9</b>	<b>14.0005.9</b>	<b>14.0006.9</b>	<b>14.0007.9</b>

